

ZÁVITY – ROZMĚROVÁ TABULKA ZÁVITŮ POUŽÍVANÝCH V POTRUBNÍCH SPOJÍCH

Měření posuvným měřidlem		Měření ověřováním		Typ závitu				
Vnější průměr (mm)	Vnitřní průměr (mm)	Počet závitů na coul	Stoupání závitu (mm)	BSP BSPT	Metrický/řad a	UNF (JIC)	ORFS UNF	NPTF NPSM
9.3-9.7	8.5-8.9	28		1/8"				
9.3-9.7	8.5-8.9	27						1/8"
9.7-9.9	8.2-8.6		1,5		M10 x 1,5			
10.9-11.1	9.7-10.0	20				7/16" - 20		
11.6-11.9	10.2-10.6		1,5		M12 x 1,5/6L			
12.4-12.7	11.3-11.6					1/2" - 20		
12.9-13.1	11.4-11.9	19		1/4"				
12.9-13.1	11.4-11.9	18						1/4"
13.6-13.9	12.2-12.6		1,5		M14 x 1,5/ 8L 6S			
14.0-14.3	12.7-13.0	18				9/16" - 18	9/16" - 18	
15.6-15.9	14.2-14.6		1,5		M16x1,5/ 10L 8S			
16.3-16.6	14.9-15.4	19		3/8"				
16.3-16.6	14.9-15.4	18						3/8"
Max.17,5	Min. 16,0						1 1/16" - 16	
17.6-17.9	16.2-16.6				M18x1,5/12L 10S			
18.7-19.0	17.3-17.6	18				3/4" - 16		
19.6-19.9	18.2-18.6		1,5		M20 x 1,5/12S			
Max.20,8	Min. 19,0						1 3/16" - 16	
20.5-20.9	18.6-19.0	14		1/2"				
20.7-21.1	18.3-18.7	14						1/2"
21.6-21.9	20.2-20.6		1,5		M22x1,5/15L 14S			
22.0-22.2	20.2-20.5	14				7/8" - 14		
22.6-22.9	20.6-21.0	14		5/8"				
23.6-23.9	22.2-22.6		1,5		M24x1,5/16S			
Max.25,4	Min. 23,6					1" - 14		
25.6-25.9	24.2-24.6		1,5		M26x1,5/18L			
26.1-26.4	24.1-24.5	14		3/4"				
26.3-26.7	23.7-24.1	14						
26.6-26.9	24.3-24.7	12			M27x 2/18L	1.1/16" - 12		3/4"
29.6-29.9	27.4-27.8		2		M30x2/22L 20S			

29.8-30.1	27.6-27.9	12				1.3/16" - 12		
29.6-29.9	28.2-28.6		1,5		M30x1,5			
32.6-32.9	30.5-30.9		2		M33x2			
33.0-33.2	30.3-30.8	11		1"				
33.0-33.3	30.8-31.2	12				1.5/16" - 12		
32.9-33.4	30.3-30.8	11,5						
35.6-35.9	33.4-33.8		2		M36x2/28L 25S			
Max.36,5	Min.34,5						1 7/16" - 12	
37.6-37.9	36.2-36.6		1,5		M38x1,5			
40.9-41.2	38.7-39.1	12				1,5/8" - 12		
41.6-41.9	39.4-39.8		2		M42x2/30S			
41.5-41.9	39.0-39.5	11		1 1/4"				
41.4-42.0	39.2-39.6	11,5						1.1/4"
Max. 42,9	Min. 40,8						1 11/16" - 12	
44.6-44.9	42.4-42.8		2		M45x2/35L			
44.6-44.9	43.2-43.6		1,5		M45x1,5			
47.3-47.6	45.1-45.5	12				1.7/8" - 12		
47.4-47.8	44.8-45.3	11		1 1/2"				
47.3-47.9	45.1-45.5	11,5						1.1/2"
Max. 50,8	Min. 48,7						2" - 12	
51.6-51.9	49.4-49.6		2		M52x2/42L 38S			
51.6-51.9	50.2-50.6		1,5		M52x1,5			
59.4-59.8	56.5-56.8	11		2"				
59.9-60.2	56.4-56.7	11,5						2"
63.3-63.6	61.3-61.8	12				2.1/2" - 12		